



# Community Antenna Protector, Low/Medium Frequency



- Robust high energy protection
- Compact package for limited space requirements
- Isolated ground prevents introduction of unwanted noise



Part Number	CATVF	CATVMF
Article Number	702535	702525
Nominal System Voltage (Un)	48 VDC	
Max Continuous Operating Voltage (Uc)	60 VDC	
Voltage Protection Level (Up)	500 V @ 5 kA	
Nominal Discharge Current (In)	5 kA 8/20 $\mu$ s	
Frequency	40 – 860 MHz	
Impedance	50 – 75 $\Omega$	
Connection Type	F-Type, Female	RF Coax, Male/Female
Ground Lead Length	120 mm	
Mounting	In-line insertion	
Temperature	-25 to 70 °C	
Depth (D)	78 mm	70 mm
Height (H)	17 mm	
Width (W)	17 mm	
Unit Weight	30 g	26 g

## WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.