


Subscriber Line Protector, Single Stage



- Single stage protection with primary or combination primary/secondary protectors
- 10 pair protector
- Simple installation into Krone[®] LSA disconnect block
- Data Line Terminator (DLT) available where screw terminal connections are required



Part Number	SLP10K1F
Article Number	701540
Max Continuous Operating Voltage (Uc)	190 VDC
Max Discharge Current (Imax), L+L-PE	20 kA 8/20 μ s
Rated Load Current (IL)	1,000 mA
Frequency	12 Hz Max
Transmission Rate	8 Mb/s
Protection Modes	L-L
Technology	Single-stage
Connection Type	Krone [®] LSA-PLUS
Impedance Balance	48 dB Max
Insertion Loss	.75 Db Max
Return Loss	22 dB Max
Loop Resistance	0.2 Ω
Temperature	-20 to 60 °C
Enclosure Material	UL [®] 94V-0 Thermoplastic
Depth (D)	21 mm
Height (H)	35 mm
Width (W)	125 mm
Unit Weight	0.02 kg
Certification Details	UL [®] 497

Krone is a registered trademark of ADC GMBH. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.