


# Subscriber Line Protector, Multi Stage



- Multi-stage protection with primary or combination primary/secondary protectors
- Single pair protector
- Provides both L-L and L-PE protection modes for comprehensive protection



Part Number	SLP1K2
Max Continuous Operating Voltage (Uc)	190 VDC
Max Discharge Current (Imax)	20 kA 8/20 $\mu$ s L+L-PE
Rated Load Current (IL)	120 mA
Frequency	3 MHz Max
Transmission Rate	2 Mb/s
Technology	Multi-stage
Connection Type	Krone <sup>®</sup> LSA-PLUS
Impedance Balance	48 dB Max
Insertion Loss	.75 Db Max
Return Loss	22 dB Max
Loop Resistance	20 $\Omega$
Temperature	-20 to 60 °C
Enclosure Material	UL <sup>®</sup> 94V-0 Thermoplastic
Depth (D)	41 mm
Height (H)	21 mm
Width (W)	10 mm
Unit Weight	0.005 kg

Krone is a registered trademark of ADC GMBH. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.