


# DIN Rail Filter Module – DFM63A



- Secondary surge protection and filtering
- DIN rail mount provides simple installation



Part Number	DFM63A
Rated Load Current (IL)	63 A
Max Continuous Operating Voltage (Uc)	275 VAC
Frequency	50 – 60 Hz
Connection, Solid	1 – 35 mm <sup>2</sup>
Connection, Stranded	1 – 25 mm <sup>2</sup>
Enclosure Material	UL <sup>†</sup> 94V-0 Thermoplastic
Enclosure Rating	IP 20 NEMA <sup>®</sup> -1
Mounting	35 mm top hat DIN rail
Module Width	4 M
Temperature	-35 to 55 °C
Unit Weight	1.57 kg
Depth (D)	68 mm
Height (H)	90 mm
Width (W)	72 mm
Standard Packaging Quantity	1 pc
UPC	78285688371

NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.