
## Modular Spark Gap Diverter – SGD1251SRNE (702426)





• Effective equipotential bonding provides N-PE equalization protection bond on TT power distribution systems







| Part Number                                  | SGD1251SRNE  |
|--|--|
| Article Number                               | 702426   |
| Nominal Discharge Current (In)               | 20 kA 8/20 μs  |
| Max Discharge Current (Imax), Per Mode       | 60 kA 8/20 μs  |
| Measured Limiting Voltage (MLV)              | 2,420 VAC  |
| Follow Current Extinguishing Capability @ Un | 100 A  |
| Impulse Current (limp)                       | 25 kA 10/350 μs  |
| Max Operating Current                        | 0.5 mA   |
| Frequency                                    | 50 – 60 Hz   |
| Protection Modes                             | N-PE   |
| Short Circuit Current Rating (SCCR)          | 25 kA  |
| Technology                                   | Encapsulated Spark Gap   |
| Connection, Solid                            | 35 mm² Max   |
| Connection, Stranded                         | 25 mm <sup>2</sup> Max   |
| Mounting                                     | 35 mm top hat DIN rail   |
| Enclosure Material                           | UL <sup>*</sup> 94V-0 Thermoplastic  |
| Enclosure Rating                             | IP 20<br>NEMA®-1   |
| Remote Contacts                              | Yes  |
| Temperature                                  | -40 to 80 °C   |
| Module Width                                 | 1 M  |
| Depth (D)                                    | 68 mm  |
| Height (H)                                   | 90 mm  |
| Width (W)                                    | 18 mm  |
| Unit Weight                                  | 0.12 kg  |
| Complies With                                | ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C<br>ANSI®/IEEE® C62.41.2-2002 Scenario II, Exposure 3, 100 kA 8/20 μs, 10 kA 10/350<br>μs |



| Part Number                 | SGD1251SRNE                    |
|-----------------------------|--------------------------------|
|                             | IEC® 61643-1 Class I, Class II |
| Replacement Module          | SGD125M                        |
| Certifications              | CE<br>cURus                    |
| Standard Packaging Quantity | 1 pc                           |
| UPC                         | 78285662252                    |
| EAN-13                      | 8711893097146                  |

ANSI is a registered trademark of American National Standards Institute. IEC is a registered trademark of the International Electrotechnical Commission. IEEE is a registered trademark of The Institute of Electrical and Electronics Engineers, Inc. NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

## WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



