


Transient Surge Filter – TSF6A240V



The ERICO CRITEC Transient Surge Filter (TSF) product family is a UL registered, IEC compliant, compact, serviceable solution for protection of PLC controllers, SCADA systems, motor control centers and other process control systems.

- Compact, space saving design
- Replaceable surge module reduces down time and unprotected time during maintenance
- Compliance to the latest UL 1449 Edition 4 and IEC 61643-11 surge standards and UL 1283 Electromagnetic Interference Filters (EMI) standard
- Low let-through voltages on the critical line to neutral mode
- Transient Discriminating (TD) Technology provides increased service life



Part Number	TSF6A240V
Nominal System Voltage (Un)	240 V
Rated Load Current (IL)	6 A
Max Continuous Operating Voltage (Uc)	275 V
Stand-off Voltage	440
Frequency	0 – 100 Hz
Max Discharge Current (Imax), L-N	20 kA 8/20 μ s
Max Discharge Current (Imax), L-PE	20 kA 8/20 μ s
Max Discharge Current (Imax), N-PE	20 kA 8/20 μ s
Filtering	-65 dB @ 100 kHz
Distribution System	1Ph 2W+G
Protection Modes	L-N L-PE N-PE
Connection, Solid	2.0 – 5.3 mm ²
Connection, Stranded	2.0 – 5.3 mm ²
Mounting	35 mm top hat DIN rail
Status Indication	Mechanical flag Remote Contacts
Enclosure Material	UL [†] 94V-0 Thermoplastic
Enclosure Rating	IP 20

Part Number	TSF6A240V
Temperature	-5 to 40 °C
Module Width	3 M
Depth (D)	95.2 mm
Height (H)	122.7 mm
Width (W)	54 mm
Unit Weight	507 g
Replacement Module	TSF240MTDS
Certifications	CE cURus
Standard Packaging Quantity	1 pc
UPC	78285679980
EAN-13	0782856799801

UL 1449 Edition 4 / UL 1283 Edition 5 Ratings					
Part Number	TSF6A24V	TSF6A120V	TSF20A120V	TSF6A240V	TSF20A240V
Max Continuous Operating Voltage (Uc)	-	170 V		275 V	
Rated Load Current (IL)	-	6 A	20 A	6 A	20 A
Nominal Discharge Current (In), L-N	-	3 kA 8/20 µs			
Nominal Discharge Current (In), L-PE	-	3 kA 8/20 µs			
Nominal Discharge Current (In), N-PE	-	3 kA 8/20 µs			
Voltage Protection Rating (VPR), L-N	-	330 V	400 V	-	-
Voltage Protection Rating (VPR), L-PE	-	900 V	800 V	-	-
Voltage Protection Rating (VPR), N-PE	-	700 V	700 V	-	-
Measured Limiting Voltage (MLV), L-N	-	-	-	620 V	680 V
Measured Limiting Voltage (MLV), L-PE	-	-	-	1450 V	1360 V
Measured Limiting Voltage (MLV), N-PE	-	-	-	1220 V	1330 V
Overcurrent Protection Fuse	-	Bussmann FNQ-R-7-1/2	Mersen ATMR25	Bussmann FNQ-R-7-1/2	Mersen ATMR25
Certification Details	-	UL® 1449 Edition 4 Type 2CA, 3 kA Mode		UL® 1449 Edition 4 Type 4CA, 3 kA Mode	
		UL® 1283 Edition 5 EMI Filter			

IEC 61643-11 Ratings					
Part Number	TSF6A24V	TSF6A120V	TSF20A120V	TSF6A240V	TSF20A240V
Max Continuous Operating Voltage (Uc)	30 V	170 V		275 V	
Rated Load Current (IL)	6 A		16 A	6 A	16 A
Nominal Discharge Current (In), L-N	3 kA 8/20 µs				
Nominal Discharge Current (In), L-PE	3 kA 8/20 µs				
Nominal Discharge Current (In), N-PE	3 kA 8/20 µs				
Voltage Protection Level (Up), L-N	330 V	330 V	330 V	800 V	850 V

IEC 61643-11 Ratings					
Part Number	TSF6A24V	TSF6A120V	TSF20A120V	TSF6A240V	TSF20A240V
Voltage Protection Level (Up), L-PE	500 V	1050 V	1050 V	1800 V	1900 V
Voltage Protection Level (Up), N-PE	500 V	1050 V	1050 V	1800 V	1900 V
Overcurrent Protection Circuit Breaker	Clipsal 4CB106/10		Clipsal 4CB116/10	Clipsal 4CB106/10	Clipsal 4CB116/10
Complies With	IEC® 61643-11 Class II				

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.