

POTENTIAL EQUALIZATION CLAMP



CERTIFICATIONS



FEATURES

High peak current capability provides long service life

Weatherproof enclosure is suitable for direct burial

The PEC100 is ATEX approved and suitable for use in potentially explosive atmospheres

SPECIFICATIONS


Product Attribute	Value
Catalog Number	PEC100
Spark-Over Voltage @ 100 V/s	350 V
Max Discharge Current (I _{max})	100 kA 8/20 μs
Technology	Gas Discharge Tube (GDT)
Insulation Resistance	1 GΩ Min
Capacitance	15 pF Max
Voltage Protection Level (Up)	800 V @ 1,000 V/μs
Impulse Current (I _{imp})	25 kA 10/350 μs
Lead Length	450 mm
Lead Size	16 mm ²

Product Attribute	Value
Enclosure Rating	IP 66 IP 67
Temperature	-30 to 70 °C
Diameter 1(Ø1)	28 mm
Diameter 2(Ø2)	16.30 mm
Length(L)	953 mm
Unit Weight	0.500 kg
Complies With	IEC® 61643-1 Class I, Class II IEC® 62561-3

ADDITIONAL PRODUCT DETAILS

Spark-over voltage has a tolerance of +/- 20%.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.