


# DT1 DIN Rail Surge Protection Class I+II, 3+0 Mode



- Compact, yet high surge rated pluggable design, using minimum DIN rail width
- External back-up fuse is not required up to 315 A
- Retaining clip ensures enhanced vibration and shock resistance performance
- Red/Green status indication and change-over contacts standard for remote monitoring



Part Number	DT130030R
Nominal System Voltage (Un)	240 V
Max Continuous Operating Voltage (Uc)	300 V
Nominal Discharge Current (In), IEC	12.5 kA 8/20 $\mu$ s
Max Discharge Current (Imax), IEC	50 kA 8/20 $\mu$ s
Impulse Current (Iimp)	12.5 kA 10/350 $\mu$ s
Voltage Protection Level (Up)	1,400 V
Back-Up Fuse @ Isccr	250 A @ 50 kA 315 A @ 25 kA
Response Time	25 ns Max
Protection Modes	L-PEN
Short Circuit Current Rating (Isccr)	25 kA 50 kA
Temporary Over Voltage 120 min (Ut/mode)	442 V Safe Fail
Temporary Over Voltage Withstand 5 s (Ut)	337 V
Nominal Discharge Current (In), UL	20 kA 8/20 $\mu$ s
Short Circuit Current Rating (SCCR)	150 kA
Voltage Protection Rating (VPR)	900 V
Technology	Thermal Disconnect
Connection, Solid	35 mm <sup>2</sup> Max
Connection, Stranded	25 mm <sup>2</sup> Max
Torque (TQ)	4.5 N-m
Humidity	5 - 95 % RH
Temperature	-40 to 70 °C
Enclosure Material	UL® 94V-0 Thermoplastic

Part Number	DT130030R
Enclosure Rating	IP 20
Mounting	35 mm top hat DIN rail
Remote Contact Switching Capacity	0.5 A @ 12 VDC 0.5 A @ 24 VDC 0.5 A @ 48 VDC 1.0 A @ 125 VAC 1.0 A @ 250 VAC
Remote Contacts	Yes
Status Indication	Mechanical flag
Depth (D)	85 mm
Height (H)	90 mm
Width (W)	54 mm
Unit Weight	0.514 kg
Certification Details	UL® 1449 Edition 4 Type 1CA
Complies With	EN 61643-11 Type 1, Type 2 IEC® 61643-11 Class I, Class II

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC. VDE is a registered trademark of VDE Verband Deutscher Elektrotechniker e.V. Corporation.

#### WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.